

Harvest the Sunshine


465W



JA SOLAR

JAM54D40 LB n-type Double Glass Bifacial Modules

Premium Cells



MBB Half-Cell
Technology

26%



Cell Conversion
Efficiency

Premium Modules



Higher power
generation better LCOE




n-type with very
Lower LID




Better Temperature
Coefficient



Better low irradiance
response



15-year product
warranty



30-year linear power
output warranty

Comprehensive Certificates


- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing



DEEP BLUE 4.0 Pro

JAM54D40 LB

n-type Double Glass Bifacial Modules



MECHANICAL PARAMETERS

	Mono
	22kg
	1762×1134mm×30mm
	4mm ² (IEC), 12 AWG(UL)
	108(6×18)
	IP68, 3diodes
	QC Solar QC4.10-351/QC4.10-35
	Stäubli PV-KST4-EVO2A/xy ,PV-KBT4-EVO2A/xy
	Portrait: 300mm(+)/400mm(-)
	Landscape: 1200mm(+)/1200mm(-)
	1.6mm/1.6mm
	36pcs/Pallet, 936pcs/40HQ Container
	China/Vietnam

Remark: customized frame color and cable length available upon request

ELECTRICAL PARAMETERS AT STC and BNPI

	JAM54D40 -440/LB	JAM54D40 -445/LB	JAM54D40 -450/LB	JAM54D40 -455/LB	JAM54D40 -460/LB	JAM54D40 -465/LB
TYPE	STC BNPI	STC BNPI	STC BNPI	STC BNPI	STC BNPI	STC BNPI
Rated Maximum Power(P _{max}) [W]	440 485	445 490	450 495	455 500	460 505	465 513
Open Circuit Voltage (V _{oc}) [V]	38.90 38.90	39.10 39.10	39.30 39.30	39.50 39.50	39.70 39.70	40.20 40.20
Maximum Power Voltage(V _{mp}) [V]	32.47 32.47	32.65 32.65	32.82 32.82	33.00 33.00	33.17 33.17	33.50 33.50
Short Circuit Current(I _{sc}) [A]	14.31 15.78	14.40 15.85	14.48 15.93	14.56 16.01	14.64 16.07	14.65 16.17
Maximum Power Current(I _{mp}) [A]	13.55 14.94	13.63 15.01	13.71 15.09	13.79 15.16	13.87 15.23	13.88 15.32
Module Efficiency [%]	22.0	22.3	22.5	22.8	23.0	23.3
Short Circuit Current (I _{sc}) [A] at BSI	17.57	17.64	17.70	17.92	17.98	18.03
Power Tolerance	0~+3%					
Temperature Coefficient of I _{sc} (α _{Isc})	+0.045%/°C					
Temperature Coefficient of V _{oc} (β _{Voc})	-0.250%/°C					
Temperature Coefficient of P _{max} (γ _{Pmp})	-0.290%/°C					
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G					
BNPI	front Irradiance 1000W/m ² , rear Irradiance 135W/m ²					
BSI	front Irradiance 1000W/m ² , rear Irradiance 300W/m ²					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.



They only serve for comparison among different module types.

Measurement tolerance at STC and BNPI: P_{max} ±3%, V_{oc} ±3% and I_{sc} ±5%.

ELECTRICAL CHARACTERISTICS WITH 10% Bifacial Gains

	JAM54D40 -440/LB	JAM54D40 -445/LB	JAM54D40 -450/LB	JAM54D40 -455/LB	JAM54D40 -460/LB	JAM54D40 -465/LB
TYPE						
Rated Max Power(P _{max}) [W]	484.0	489.5	495.0	500.5	506.0	511.5
Open Circuit Voltage(V _{oc}) [V]	38.90	39.10	39.30	39.50	39.70	40.20
Max Power Voltage(V _{mp}) [V]	32.47	32.65	32.82	33.00	33.17	33.50
Short Circuit Current(I _{sc}) [A]	15.74	15.84	15.93	16.02	16.10	16.12
Max Power Current(I _{mp}) [A]	14.91	14.91	14.99	15.17	15.26	15.27

CHARACTERISTICS



OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Maximum Static Load, Front	3600Pa,1.5
Maximum Static Load, Back	1600Pa,1.5
NOCT	45±2°C
Bifaciality	φP _{max} (80±10) %, φV _{oc} (98±5) %, φI _{sc} (80±10) %
Safety Class	Class II
Fire Safety Class	Class C



Headquarters

JA Solar Technology Co., Ltd.
No. 123 Xinxing Road, 055550 Ningjin County, Hebei Province,
PEOPLE'S REPUBLIC OF CHINA

Specifications subject to technical changes and tests.
JA Solar reserves the right of final interpretation.

Version No. : Aus-EN-20250109A