

Certificate of Conformity

Certificate Number: CN-PV-210187

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specifications /standards at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant Name & Address: Shenzhen SOFARSOLAR Co., Ltd.

401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community,

XinAn Street, BaoAn District, Shenzhen, China

Product Description: Solar Grid-tied Inverter

Ratings & Principle See Annex to Certificate of Conformity

Characteristics:

Models/Type References: SOFAR 3.3KTLX-G3, SOFAR 4.4KTLX-G3, SOFAR 5KTLX-G3-A

SOFAR 5.5KTLX-G3, SOFAR 6.6KTLX-G3, SOFAR 8.8KTLX-G3, SOFAR 8.8KTLX-G3-A, SOFAR 11KTLX-G3, SOFAR 10KTLX-G3-A

SOFAR 11KTLX-G3-A, SOFAR 12KTLX-G3

Brand Name: 5 FAR

Specification/Standard: NRS 097-2-1:2017 Edition 2.1

GRID INTERCONNECTION OF EMBEDDED GENERATION

PART 2: SMALL-SCALE EMBEDDED GENERATION

SECTION 1: UTILITY INTERFACE

Certificate Issuing Office Intertek Testing Services Ltd. Shanghai

Name & Address: West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot Free

Trade Zone, Shanghai, P. R. China

Test Report Number: 210715145GZU-004

Additional information in Appendix.

Signature

Certification Manager: Grady Ye

/ sunta

Date: 10 August 2021



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210187

MODEL	SOFAR 3.3KTLX- G3	SOFAR 4.4KTLX- G3	SOFAR 5KTLX- G3-A	SOFAR 5.5KTLX- G3	
Max PV voltage	1100Vdc				
MPPT Voltage range	140-1000Vdc				
Max. input current	15/15A				
PV Isc	22.5/22.5A				
Rated power(W)	3000	4000	5000	5000	
Max.apparent power (VA)	3300	4400	5000	5500	
Max output current	3×5.0 A	3×6.7 A	3×7.6 A	3×8.3 A	
Output voltage	3W/N/PE 230Vac/400Vac				
Nominal Frequency	50 Hz				
Power Factor	1 default (adjustable+/-0.8)				
Ambient Temperature	-30℃ - +60℃				
Protection Degree	IP65				
Protection Class	Class I				
Software Version	V000001				



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210187

MODEL	SOFAR 6.6KTLX- G3	SOFAR 8.8KTLX- G3	SOFAR 8.8KTLX- G3-A	SOFAR 10KTLX- G3-A	
Max PV voltage	1100Vdc				
MPPT Voltage range	140-1000Vdc				
Max. input current	15/15A		15/30A		
PV Isc	22.5/22.5A		22.5A/45A		
Rated power(W)	6000	8000	8000	10000	
Max.apparent power (VA)	6600	8800	8800	10000	
Max output current	3×10.0 A	3×13.3 A	3×13.3 A	3×15.2 A	
Output voltage	3W/N/PE 230Vac/400Vac				
Nominal Frequency	50 Hz				
Power Factor	1 default (adjustable+/-0.8)				
Ambient Temperature	-30℃ - +60℃				
Protection Degree	IP65				
Protection Class	Class I				
Software Version	V000001				



APPENDIX: Certificate of Conformity

This is an Appendix to Certificate of Conformity Number: CN-PV-210187

MODEL	SOFAR 11KTLX-G3	SOFAR 11KTLX-G3-A	SOFAR 12KTLX-G3	
Max PV voltage	1100Vdc			
MPPT Voltage range	140-1000Vdc			
Max. input current	15A/15A 15A/30A			
PV Isc	22.5/22.5A 22.5A/45A			
Rated power(W)	10000	10000	12000	
Max.apparent power (VA)	11000	11000	13200	
Max output current	3×16.7 A	3×16.7 A	3×20.0 A	
Output voltage	3W/N/PE 230Vac/400Vac			
Nominal Frequency	50 Hz			
Power Factor	1 default (adjustable+/-0.8)			
Ambient Temperature	-30℃ - +60℃			
Protection Degree	IP65			
Protection Class	Class I			
Software Version	V000001			